RECOVERING TIME-VARYING NETWORKS FROM SINGLE-CELL DATA

Euxhen Hasanaj¹ Barnabás Póczos¹ Ziv Bar-Joseph^{1,2}

¹Machine Learning Department, Carnegie Mellon University, Pittsburgh, PA 15213, USA ²Computational Biology Department, Carnegie Mellon University, Pittsburgh, PA 15213, USA {ehasanaj,bapoczos,zivbj}@cs.cmu.edu

Abstract

Gene regulation is a dynamic process that underlies all aspects of human development, disease response, and other key biological processes. The reconstruction of temporal gene regulatory networks has conventionally relied on regression analysis, graphical models, or other types of relevance networks. With the large increase in time series single-cell data, new approaches are needed to address the unique scale and nature of this data for reconstructing such networks. Here, we develop a deep neural network, Marlene, to infer dynamic graphs from time series single-cell gene expression data. Marlene constructs directed gene networks using a self-attention mechanism where the weights evolve over time using recurrent units. By employing meta learning, the model is able to recover accurate temporal networks even for rare cell types. In addition, Marlene can identify gene interactions relevant to specific biological responses, including COVID-19 immune response, fibrosis, and aging.

1 INTRODUCTION

Biological systems are dynamic, changing over time in response to various stimuli and events. To construct accurate models of biological activity during development, disease progression, treatment response, and other biological processes, it is essential to track their evolution over time (Bar-Joseph et al., 2012). Studying the *regulation* of these dynamic processes is key for understanding the underlying mechanisms that drive the response and for identifying potential interventions that can serve as cures for diseases (Silverman et al., 2020).

Much of the research in this area is focused on the reconstruction of regulatory networks (Karlebach & Shamir, 2008; Badia-I-Mompel et al., 2023). These networks comprise a subset of proteins known as transcription factors (TFs), which regulate the activity of all other genes and proteins within the cell. However, these gene regulatory networks (GRNs) are not static. Instead, both the active nodes (proteins) and the edges (genes) change over time (Gasch et al., 2000; Luscombe et al., 2004). To reconstruct such networks, researchers often integrate static data—such as the type of nodes in the network—with dynamic data, such as time series measurements of node activity (gene expression profiles). Early work in this area employed microarrays and ChIP-chip data (Lee et al., 2002; Wang et al., 2006; Blais & Dynlacht, 2005; Gilchrist et al., 2009) followed by time series next-generation RNA-seq data (Wang et al., 2009), and most recently, single-cell RNA-seq (scRNA-seq) data (Ding et al., 2022; Nguyen et al., 2021; Matsumoto et al., 2017b).

Several computational methods have been proposed over the last two decades to reconstruct such dynamic GRNs (Bar-Joseph et al., 2003; Yosef et al., 2013; Schulz et al., 2012; Yan et al., 2021). Some of these methods utilized time-varying graphical models including Hidden Markov models, Markov random fields, and Dynamic Bayesian Networks (Ahmed & Xing, 2009; Song et al., 2009; Dondelinger et al., 2013; Zhu & Wang, 2015). Other approaches attempted to use regression or to learn temporal precision matrices using extensions of the graphical lasso algorithm (Wang et al., 2020; Hallac et al., 2017).

While such models successfully reconstructed some processes (Ahmed & Xing, 2009; Kim et al., 2012), they are less suitable for the more recent types of data, most notably scRNA-seq time series data. First, the much larger size of the data presents a challenge for traditional graphical models. In

addition, prior methods do not directly account for the fact that multiple cells are profiled for each time point. Finally, prior methods do not utilize the ability to learn much larger models such as neural networks which have been shown to improve many other learning tasks (Ching et al., 2018; Angermueller et al., 2016).

Very recently, a few methods have been proposed for using deep learning to recover static GRNs (Shrivastava et al., 2022; Shu et al., 2021). However, they cannot be directly used to capture dynamic GRNs (i.e., enforcing learning between time points). Two recent approaches, Dictys and CellOracle (Wang et al., 2023b; Kamimoto et al., 2023) can be used to infer dynamic GRNs, however, these methods rely on a different type of data (ATAC-seq) which is harder to obtain and less prevalent.

Beyond the realm of biology, the inference of dynamic graphs using neural networks has garnered significant attention. This problem has found applications in diverse domains, including information retrieval, molecular graphs, and traffic forecasting (Zhu et al., 2021; Zhang et al., 2020). While there are similarities between these problems and the dynamic GRN problem, there are also significant differences that make it hard to extend these methods for time series scRNA-seq. The problem of inferring temporal graphs is usually defined by recovering a series of graph adjacency matrices $\mathbf{A}_t \in \mathbb{R}^{n \times n}$ where *n* is the number of nodes and each node is a *k*-dimensional feature vector. However, when dealing with scRNA-seq data, the problem becomes: given a gene expression matrix $\mathbf{X}_t \in \mathbb{R}^{c \times g}$, where *c* is the number of cells (samples) and *g* is the number of genes (features), we are interested in recovering gene networks $\mathbf{A}_t \in \mathbb{R}^{g \times g}$, i.e., graphs of features rather than nodes (cells).

In this paper, we present a novel deep learning framework that effectively addresses the challenges discussed above for reconstructing dynamic GRNs. Our contribution is three-fold. First, we demonstrate that existing deep learning methods for temporal graph structure learning can be adapted for scRNA-seq data analysis. To achieve this, we perform a gene featurization step by leveraging set-like architectures such as DeepSets or Set Transformers (Zaheer et al., 2017; Lee et al., 2019). Second, we construct dynamic graphs by applying a self-attention mechanism (Bahdanau et al., 2014) to these gene feature vectors. To model dynamics, we draw inspiration from EvolveGCN where a gated recurrent unit (GRU) evolves the weights of a graph neural network (Pareja et al., 2020). However, unlike EvolveGCN, our approach uses a GRU to evolve the weights of key and value projection matrices in the self-attention module. This allows for the construction of dynamic graphs that capture regulatory interactions over time. Lastly, GRNs are highly dependent on cell functions, hence, separate GRNs need to be learned for each cell type. A single scRNA-seq dataset may combine cells of multiple types, some of which are rare cell populations. To this end, we employ a model-agnostic meta-learning (MAML) (Finn et al., 2017) training procedure by treating each cell type as a "task" to be learned. With this approach, the model quickly adapts to tasks with few samples, enabling the reconstruction of dynamic graphs even for rare cell types.

We apply our **meta** learning approach for inferring temporal gene regulatory networks (Marlene) to three publicly available scRNA-seq datasets. The first is a time series SARS-CoV-2 mRNA vaccination dataset of human peripheral blood mononuclear cells (PBMCs) (Zhang et al., 2023). The second dataset is a human lung aging atlas from the Human Cell Atlas Project (Regev et al., 2017; Sikkema et al., 2023). The third dataset is from a study of lung fibrosis using a mouse lung injury model (Strunz et al., 2020). All three datasets incorporate several time points, thus enabling a longitudinal analysis of the relevant biological responses through the inference of dynamic, cell type-specific GRNs. As we show, our method is able to reconstruct accurate networks for these datasets, significantly improving upon prior methods proposed for this task.

2 Methods

2.1 PROBLEM SETUP

Consider a gene expression matrix $\mathbf{X} \in \mathbb{R}^{c \times g}$ where *c* is the number of cells and *g* is the number of genes. In the human genome, *g* varies from 25,000 to 30,000, while the number of cells could be between a couple thousand to a few million. In the setting of dynamic graphs, we assume the existence of a time point for each row (cell), leading to a time series $\widetilde{\mathbf{X}} := {\mathbf{X}_1, \dots, \mathbf{X}_T}$ with $\mathbf{X}_t \in \mathbb{R}^{c_t \times g}$. Here, the number of cells c_t may vary with *t*. We are interested in recovering a series of directed graphs $\widetilde{\mathcal{G}} := {\mathcal{G}_1, \dots, \mathcal{G}_T}$ where each $\mathcal{G}_t = {\mathcal{N}, \mathcal{E}_t}$. The set of nodes is the set of genes, i.e., $\mathcal{N} = [g]$, and we assume this set is static over time. The dynamic edge sets



Figure 1: Overview of Marlene. Marlene takes as input gene expression data in the form of a cellby-gene matrix. It then performs gene featurization via the pooling by multihead attention (PMA) mechanism which returns a gene feature matrix. This matrix is then inputted into a self-attention module to obtain a gene network in the form of an adjacency matrix. The weights of the selfattention module evolve from one time point to the next via a gated recurrent unit (GRU). The expression of transcription factors and the recovered graph are used to reconstruct the full gene expression vector. Finally, the reconstructed matrix is used to predict the cell type for the batch. The network is trained in a model-agnostic meta-learning fashion where each cell type is treated as a "task" to be learned, thus enabling the model to quickly adapt to cell types with low representation.

 $\mathcal{E}_t = \{(u, v, w)\}_{u,v \in \mathcal{N}, w \in \mathbb{R}}$ denote directed weighted links between genes, where the source u is the gene that regulates the expression of its target v, and w is the strength of this relationship. The source nodes are called transcription factor genes (TFs).

We can alternatively characterize each graph \mathcal{G}_t by the corresponding adjacency matrix $\mathbf{A}_t \in \mathbb{R}^{g \times g}$. Denote $\widetilde{\mathbf{A}} := {\mathbf{A}_1, \dots, \mathbf{A}_T}$. Since TFs control the expression of their target genes, the underlying GRNs should, in principle, allow the recovery of the full expression profile for a cell. In other words, $\widetilde{\mathbf{X}} = f(\widetilde{\mathbf{X}}^{\text{TF}}, \widetilde{\mathbf{A}})$ where $\widetilde{\mathbf{X}}^{\text{TF}}$ denotes the expression of all TFs. The function f is unknown as it involves intricate interactions among genes, including combinatorial effects. For instance, certain scenarios exist where TFs cooperate with each-other to activate a gene, while in other instances, the activation requires some TFs to be active and others to be inactive (Wise & Bar-Joseph, 2015).

In existing deep learning literature, f is sometimes modeled using autoencoders (Seninge et al., 2021; Shu et al., 2021; Wang et al., 2023a). However, reconstructing the full gene expression vector is challenging as the data is extremely sparse and conventional reconstruction losses, such as mean squared error, tend to emphasize overall averages. Since GRNs are dependent on cell function, we hypothesize that simplifying the problem by predicting cell types may improve the accurate recovery of GRNs. In other words, given a temporal batch of cells of the same type $\tilde{x}^{TF} \in \mathbb{R}^{T \times \text{batch size} \times n. TFs}$, we consider the classification problem $y = f(\tilde{x}^{TF}, \tilde{\mathbf{A}})$ where y is the known cell type label for the batch. Finally, the task of learning $\tilde{\mathbf{A}}$ given a batch \tilde{x} becomes

$$\underset{\widetilde{\mathbf{A}}}{\arg\min} \operatorname{CrossEntropyLoss}(y, f(\widetilde{x}^{\mathrm{TF}}, h(\widetilde{x}))), \qquad \widetilde{\mathbf{A}} := h(\widetilde{x}) \tag{1}$$

for choices of functions f and h.

2.2 ARCHITECTURE OF MARLENE

In this work, we propose a neural network architecture called Marlene that effectively learns dynamic GRNs (Figure 1). Marlene consists of three main steps. The first two steps address the choice of h in (1), while the last addresses the choice of f. In the first step, we apply a gene featurization step by treating a batch of cells as a set of elements. The DeepSet architecture introduces a pooling operator that allows the neural network to be invariant to the order of input samples, effectively treating the input as a set (Zaheer et al., 2017). Similarly, the Set Transformer architecture is designed to process sets of data via attention-based operators that are permutation invariant (Lee et al., 2019). Specifically, the pooling by multihead attention (PMA) aggregation scheme introduced in Set Transformers outputs a matrix of k vectors $\mathbf{H} \in \mathbb{R}^{k \times g}$ for an arbitrary input set $\mathbf{X} \in \mathbb{R}^{c \times g}$. Each of the k output vectors has a specific meaning such as statistics of the input data. By applying the PMA operator to a temporal batch of cells, we obtain a gene-by-feature matrix $\mathbf{G} = \mathbf{H}^{\top} \in \mathbb{R}^{g \times k}$ that encodes information about the cells from each time point. PMA consists of a multihead attention block (MAB) where the input \mathbf{X} consists of key vectors, and the query is a learnable set of k vectors \mathbf{S} . In this work, we use a shared PMA layer for all time points assuming that the specific key statistical properties are invariant (though their value obviously changes for different time points). Given $\tilde{x} = [x_1, \ldots, x_T]$, we have

$$\widetilde{\mathbf{G}} = \mathrm{PMA}(\widetilde{x})^\top := \mathrm{MAB}(\mathbf{S}, \widetilde{x})^\top := (\mathbf{M} + \mathrm{rFF}(\mathbf{M}))^\top$$
(2)

where $\mathbf{M} = \mathbf{S} + \text{Multihead}(\mathbf{S}, \tilde{x}, \tilde{x})$ and rFF is a row-wise feedforward layer. For completeness, these operations are defined in the appendix.

Note that if cells of different types are mixed in the same batch, the statistics derived by the PMA step may not capture cell type-specific information. Consequently, in a single batch, we only include cells of one type.

In the second step, Marlene learns temporal adjacency matrices using a self-attention mechanism. To model dynamics, we draw inspiration from EvolveGCN which performs model adaptation using a GRU (Pareja et al., 2020). Unlike EvolveGCN, which uses the GRU to update the weights of a graph convolution layer, we use a GRU to evolve the key and query projection weights of the self-attention module. Since most time series we deal with contain very few time points, a GRU should suffice and not suffer from vanishing gradient problems. Similar to EvolveGCN, we apply a summarization step via top k pooling to reduce the gene feature matrix to a square matrix for the GRU (appendix).

More precisely, we initialize self-attention weights $\mathbf{W}_0^Q, \mathbf{W}_0^K \in \mathbb{R}^{k \times k}$ and two recurrent units $\text{GRU}_Q, \text{GRU}_K$. Given the time sequence of gene feature matrices $\widetilde{\mathbf{G}}$ obtained from the previous step, temporal adjacency matrices are constructed in the following recurrent fashion for all $t \in [T]$:

$$\mathbf{Z}_t = \operatorname{TopK}(\mathbf{G}_t) \tag{3}$$

$$\mathbf{W}_{t}^{Q} = \operatorname{GRU}_{Q}(\mathbf{Z}_{t}, \mathbf{W}_{t-1}^{Q}), \quad \mathbf{W}_{t}^{K} = \operatorname{GRU}_{K}(\mathbf{Z}_{t}, \mathbf{W}_{t-1}^{K})$$
(4)

$$\mathbf{Q}_t = \mathbf{G}_t \mathbf{W}_t^Q, \quad \mathbf{K}_t = \mathbf{G}_t \mathbf{W}_t^K \tag{5}$$

$$\mathbf{A}_{t} = \operatorname{softmax}\left(\frac{\mathbf{Q}_{t}\mathbf{K}_{t}^{\top}}{\sqrt{k}}\right).$$
(6)

Here, \mathbf{W}_t^Q and \mathbf{W}_t^K serve as hidden states for the respective GRUs. The GRUs dynamically adapt self-attention weights, influencing which TFs specific genes should attend to in subsequent time steps. Consequently, the evolution of these weights is constrained. We also restrict the columns of \mathbf{A}_t (i.e., sources) to p known TFs in the TRRUST database (Han et al., 2018) which greatly reduces the number of parameters to be learned. Therefore, in our implementation $\mathbf{A}_t \in \mathbb{R}^{g \times p}$.

Next, we perform a gene expression reconstruction step based on the expression of TFs and the inferred adjacency matrices. This is followed by any number of fully connected layers with nonlinear activation functions σ . Finally, we sum across output vectors to obtain a logit vector with the same dimension as the number of cell types in the data:

$$\tilde{y} = \text{Pool}(\text{Linear}(\dots \sigma(\text{Linear}(\tilde{x}^{\text{TF}} \tilde{\mathbf{A}}^{\top})))).$$
(7)

Network depth can be introduced at all three levels by stacking MAB layers during gene featurization, stacking GRUs, or stacking linear layers at the end.

2.3 META LEARNING FOR RARE CELL TYPES

ScRNA-seq datasets often originate from biological samples that exhibit cellular heterogeneity, potentially containing multiple distinct cell types. Some of these cell subpopulations are rare and are

| | | | | | 1 7 | |
|------------|------------|--------------------|-----|------------|---------------------------------|---------------|
| | Number of | | | | Metadata | |
| Dataset | Cells | Genes ¹ | TFs | Cell Types | Time Points | Sample |
| SARS-CoV-2 | 113,271 | 1899 | 556 | 7 | d0, d2, d10, d28 | PBMCs (human) |
| HLCA | $27,953^2$ | 2433 | 674 | 11 | Ages $< 35, 35 - 50, \ge 50$ | lung (human) |
| Fibrosis | 22,758 | 1217 | 433 | 6 | PBS, d3, d7, d10, d14, d21, d28 | lung (mouse) |

Table 1: Time series scRNA-seq datasets used in this study.

¹ Only showing the number of genes overlapping with the TRRUST database.

 2 We randomly sampled cells from 11 cell types.

represented by a small number of cells in the sample (Jindal et al., 2018). Since we are concerned with the discovery of cell type-specific temporal GRNs, learning such large graphs for these rare cell types may not be feasible and lead to overfitting. Since many interactions are shared across cell types (Chasman & Roy, 2017), we employ the model-agnostic meta-learning framework (MAML) (Finn et al., 2017). MAML is specifically designed to enable neural networks to adapt to novel tasks with limited training samples (i.e., few shot learning). By treating each cell type as a "task", the MAML training paradigm facilitates the recovery of dynamic graphs for rare cell types. We begin by adapting model parameters through multiple optimization steps using a batch of support examples (cells). These adapted parameters are then evaluated on a separate set of query cells, followed by a meta-update.

During the adaptation step, we perform gradient descent, while for the meta-update, we employ the Adam optimizer (Kingma & Ba, 2014). During training, gradient clipping proves crucial to prevent overfitting of the MAML adaptation step to the cell type under consideration.

3 EXPERIMENTS

To validate our approach, we use three public scRNA-seq datasets (Table 1): a human SARS-CoV-2 mRNA vaccination dataset, a lung aging atlas (The Human Lung Cell Atlas—HLCA), and a mouse lung fibrosis dataset (Zhang et al., 2023; Sikkema et al., 2023; Strunz et al., 2020). To assess the quality of the inferred networks, we draw upon two databases of TF-gene regulatory interactions, which have been curated from the scientific literature—TRRUST and RegNetwork (Han et al., 2018; Liu et al., 2015). For the human genome, TRRUST contains 8427 unique validated regulatory edges, while RegNetwork contains 150,405. Note that certain edges lack a corresponding TF or gene in the expression data, so the numbers used for the analysis are smaller. We used only the genes that were present in TRRUST for all three datasets. For the mouse lung dataset we used the corresponding mouse networks for both databases. To match the number of links in these databases, we selected the top 2% of edges for all methods. For Marlene, this was done by sparsifying the self-attention matrix to retain only the top scoring edges. The significance of the overlap was carried out via Fisher's exact test (Fisher, 1922). All *p*-values were corrected for multiple testing using the Benjamini-Hochberg procedure (Benjamini & Hochberg, 1995).

We compare Marlene against several popular static gene regulatory network inference methods included in the BEELINE benchmark (Pratapa et al., 2020) and beyond, such as PIDC, GENIE3, GRNBoost2, SCODE, and DeepSEM (Chan et al., 2017; Huynh-Thu et al., 2010; Moerman et al., 2019; Matsumoto et al., 2017a; Shu et al., 2021), which are applied independently to each time point. DeepSEM is a deep generative model based on structural equation modeling. We also compare against time-varying graphical lasso (TVGL)¹, a method that models temporal precision matrices (Hallac et al., 2017), and to a deep neural network that utilizes the S4 module (GraphS4mer) (Tang et al., 2022; Gu et al., 2021).

We train Marlene using a batch size of 16 cells and also set the number of seeds in the PMA layer to 16. For MAML, we use 5 inner steps. The model with the lowest loss is selected for GRN inference. For the meta-update, we use a decaying learning rate starting with 1e-4, while for the inner step we use 1e-3 for both datasets. Experiments were performed using an NVIDIA RTX 3060 and took only a few minutes per run.

¹We used the implementation of https://github.com/fdtomasi/regain



Figure 2: Overlap analysis of the SARS-CoV-2 vaccination dataset. Showing $-\log_{10}(FDR)$ values from a Fisher's exact test measuring the overlap between predicted TF-gene interactions in reconstructed networks and two TF-gene interaction databases (TRRUST, RegNetwork). Best performing method is starred.

3.1 CASE STUDY 1: SARS-COV-2 VACCINATION

The SARS-CoV-2 vaccination dataset consists of peripheral blood mononuclear cells (PBMCs) from six healthy donors at four time points (days 0, 2, 10, and 28) (Zhang et al., 2023). Day 0 samples were obtained before vaccination. We removed the "Other" cell type group and kept the remaining seven. These include B cells, dendritic cells (DC), monocytes (Mono), natural killer cells (NK), and various types of T cells.

3.1.1 MARLENE RECOVERS ACCURATE GENE REGULATORY NETWORKS

Analysis results using Marlene and prior methods is presented in Figure 2. As can be seen, Marlene outperformed competing methods in the dynamic GRN inference task for 5 of the cell types, yielding statistically significant results across time points. Specifically, for B cells, Marlene successfully identified more than 800 regulatory links within the RegNetwork framework at each time point (FDR $\leq 1e-67$), surpassing the performance of the second-best method, SCODE, which detected 579 links (day 2, FDR $\leq 1e-15$). Analogous findings were observed for natural killer cells, where Marlene identified over 600 RegNetwork links at each time point (FDR $\leq 1e-18$). In comparison, the second-ranking method, SCODE, showed a significant overlap for only one time point (day 28). Upon examining the TRRUST database, we observed less pronounced differences in the results. Nonetheless, Marlene obtained higher overlap for 5 out of 7 cell types followed by GENIE3, which performed well for monocytes and the "Other T" category.

3.1.2 MARLENE RECOVERS REALISTIC DYNAMIC TRANSITIONS

The analysis so far has primarily focused on individual time points. Next, we turned our attention to assessing the quality of graph transitions between consecutive time points. Specifically, we examined whether the learned graphs demonstrated smooth transitions over time. To evaluate this, we computed the intersection-over-union (IoU) score for edges between time points t and t + 1(Figure 3a). Notably, our findings revealed that for most cell types, Marlene exhibited the lowest IoU score during the initial period (days $0 \rightarrow 2$), followed by higher scores during days $2 \rightarrow 10$, and $10 \rightarrow 28$. This pattern aligns with our expectations, as variations in gene expression are likely to be most pronounced during the early post-vaccination period (days $0 \rightarrow 2$). From the methods



Figure 3: Temporal analysis of the predicted gene regulatory networks for the SARS-CoV-2 vaccine dataset. (a) Intersection-over-union (IoU) scores between consecutive graphs. (b) For each method, top 3 MSigDB terms enriched for genes that were regulated at day 2 but not day 0.

we compare against, GENIE3, GRNBoost2, SCODE, PIDC, and DeepSEM exhibited significantly lower IoU scores across all temporal transitions, likely due to their lack of dynamic modeling and the fact that they were ran independently per time point. TVGL, on the other hand, showed high IoU scores which remained close to constant over time. Finally, Graphs4mer displayed a reduction in IoU scores over time, which is unlikely given the expected immediate immune response.

Next, we sought to assess the quality of the TF-gene regulatory links added between time points. For brevity, we focused specifically on the initial temporal transition (days $0 \rightarrow 2$), as this period is likely to witness a more significant biological response. For each cell type, we took note of all the genes that were regulated by some TF at day 2 but not at day 0. Using this set of genes *z*, we performed gene set enrichment analysis (GSEA) (Subramanian et al., 2005; Fang et al., 2023) using the molecular signatures database (MSigDB) (Liberzon et al., 2015). Through permutation tests, GSEA assigns an enrichment score (ES) to *z* reflecting its overrepresentation within the MSigDB gene set collection. We found that for many cell types, genes added by Marlene at day 2 greatly overlapped with COVID-19 and SARS-CoV-2 related gene sets. For instance "Interferon Gamma



Figure 4: Results on the HLCA dataset. (a) FDR corrected *p*-values of Fisher exact tests reflecting the number of links that overlap with TRRUST and RegNetwork databases. (b) Top 3 Jensen Diseases terms enriched for genes added between the first and second age group.

Response", which was identified as a SARS-CoV-2 antiviral response (Hilligan et al., 2023), was significantly enriched in dendritic cells (15 genes, FDR = 1e-6). Similarly, "TNF-alpha Signaling via NF-kB"—a pathway involved in the immune response and inflammation (Hayden & Ghosh, 2011)—was enriched in several cell types, as well as processes such as "Apoptosis" (cell death) and "p53 Pathway" (inhibits replication of infected cells) (Elmore, 2007; Harris & Levine, 2005). Other methods, while being enriched for relevant terms, showed a smaller gene overlap for these types (Figure 3b) or were not consistent across cell types (e.g., DeepSEM, SCODE).

Overall, these results suggest that Marlene is able to capture both known TF-gene links, but also genes that are relevant to the response being studied.

3.2 CASE STUDY 2: AGING AND SENESCENCE IN THE LUNG

The Human Lung Cell Atlas (HLCA) is a large data integration effort by the Human Cell Atlas Project (Sikkema et al., 2023; Regev et al., 2017). This data combines scRNA-seq samples from 107 individuals spanning an age range of 10 to 76 years, making it particularly attractive for studying aging and senescence (a form of aging characterized by the absence of cell division) (van Deursen, 2014; SenNet Consortium, 2022).



Figure 5: Enrichment for senescence using the SenMayo set. For 4 cell types, there was statistically significant enrichment for the oldest age group. We only used the top 200 regulated genes.

We split the atlas into three age groups at 35 and 50 years old, thus forming a pseudotime series of length 3. We removed smokers from the dataset as these will likely confound the results. To accommodate the data in the GPU, we randomly selected cells from 11 cell types, including type II pneumocytes, endothelial cells, and monocytes.

Similar to the vaccination dataset, we begin the analysis by evaluating the set of regulatory links using the TRRUST and RegNetwork databases. For this dataset we find that Marlene and SCODE are the top two performing methods (Figure 4a). For some of the cell types, Marlene achieves significant results, recovering more than 1000 RegNetwork links (classical monocytes, FDR = 1e-76). Even for cell types with fewer cells, such as non-classical monocytes (with only 138 cells for the second age group), Marlene still recovered more than 800 known TF-gene links for each transition (FDR $\leq 1e-27$). SCODE performed well for some cell types such as CD1c-positive myeloid dendritic cells and CD4-positive, alpha-beta T cells. For all other methods, the overlap was smaller (Appendix Figure 6a). Note that while SCODE is comparable for the static network (single time point) inference task, it does not utilize dynamic information.

We next examined the ability of different methods to capture the dynamics of the biological processes. For this, we looked at graph transitions. IoU scores show that only the temporal methods (Marlene, TVGL, Graphs4mer) capture the smooth temporal transition between time points, while other methods, including SCODE, achieve low IoU scores (Appendix Figure 6b). We performed GSEA using Jensen Diseases gene set to see if genes added by Marlene in these transitions were enriched for any age-related diseases (Pletscher-Frankild et al., 2015; Grissa et al., 2022). We found that Marlene added genes are enriched for several diseases such as arthritis, lung disease, and coronary artery disease. Other dynamic baselines were also enriched for relevant terms, but contained fewer marker genes (Figure 4b).

Finally, we also investigated whether the genes regulated at different age groups were enriched for senescence. Cellular senescence refers to a permanent arrest of cell division triggered by the accumulation of DNA damage (Suryadevara et al., 2024). The absence of cell division can detrimentally impact tissue regeneration and repair, thereby contributing to various age-related diseases. Here, we use the SenMayo gene set which contains 125 genes reported to be enriched for senescence (Saul et al., 2022). Only 81 of these genes overlapped with our data. We found that for 4 cell types, there was an increase in SenMayo gene regulation at the oldest age group (age > 50), suggesting that senescent cells accumulate with age as hypothesized (Figure 5).

3.3 CASE STUDY 3: FIBROSIS IN A MOUSE LUNG INJURY MODEL

Next, we evaluated whether Marlene could perform effectively across different species by analyzing a dataset from a mouse model of lung injury induced by the chemotherapeutic agent bleomycin (Strunz et al., 2020). The dataset included seven time points: one pre-treatment and six post-

treatment intervals. After filtering out cell types with low representation and genes with low counts, we retained six cell types, including B cells, T cells, and macrophages.

In this analysis, Marlene outperformed competing methods in four of the six cell types when benchmarked against the RegNetwork database, specifically in alveolar epithelial cells, dendritic cells, endothelial cells, and macrophages. For T cells, TVGL showed slightly better performance. When evaluated against the TRRUST database, SCODE performed well in four cell types, while Marlene surpassed it in the remaining two. The differing results between two databases may reflect their incomplete coverage, highlighting the need for further refinement.

Finally, all static baselines, including SCODE, showed low IoU scores across time points, indicating their inability to capture temporal evolution. In contrast, Marlene, showed increasing IoU scores over time, suggesting ongoing lung regeneration following treatment which slowly stabilizes. Figures illustrating these findings are provided in the appendix.

4 DISCUSSION

Gene regulation is a dynamic process that underlies all biological systems and responses. Understanding which TFs regulate which genes, and when this regulation occurs, provides insights into these dynamic processes which can ultimately lead to better treatment options.

To improve on current methods for reconstructing time varying regulatory networks, we use the expressive capabilities of deep neural networks to model the dynamic regulation of genes. Specifically, we focused on inferring dynamic networks from scRNA-seq data.

Our proposed method, Marlene, constructs dynamic graphs from time series data. Marlene begins with a set pooling operator based on PMA to extract gene features. These gene features are subsequently used to construct dynamic graphs via a self-attention mechanism. The weights of the self-attention block are updated through the use of GRUs. Additionally, by employing MAML, we help Marlene uncover graphs even for rare cell types However, Marlene optimizes the prediction of cell type label rather than gene expression. As such, Marlene is not currently equipped to determine the impact of perturbations including gene knockouts or overexpression experiments. Exploring the integration of causal inference capabilities into Marlene represents a promising direction for future research.

We demonstrated the effectiveness of Marlene in recovering dynamic GRNs using three datasets: a SARS-CoV-2 vaccination dataset, a lung aging atlas, and a mouse dataset of fibrosis. In all three datasets, Marlene successfully identified many validated TF-gene links from the TRRUST and Reg-Network databases across various cell types. It also accurately modeled the temporal dynamics of these connections. Some prior methods ignored the temporal aspect, leading to very little similarity between consecutive time networks. Other methods integrated all time points together, leading to very similar networks for each time point. In contrast, Marlene accurately recovered the variation dynamics, which is often characterized by strong rewiring following treatment that later stabilizes. In addition, Marlene identified many relevant edges. For instance, in the lung aging data, several dynamic edges were enriched for age-related diseases, such as arthritis. Meanwhile, in the SARS-CoV-2 data, these dynamic links were enriched for immune response processes. Prior methods captured some known edges, however, the overall results were less significant. By providing better models to explain disease and vaccine response, researchers can zoom in on the specific mechanisms targeted which in turn can lead to better treatments.

5 LIMITATIONS

While successful, Marlene has a few limitations. The datasets we used in this study, while typical for scRNA-seq time series, consisted of only a few time points. For longer sequences, the GRU operation may suffer from vanishing gradient problems (Pascanu et al., 2012). In such scenarios, the S4 module may be preferred as it has been shown to model long sequences better than traditional GRUs (Gu et al., 2021). In addition, using a large number of genes for training, results in quadratic growth in memory consumption due to the need to store adjacency matrices. This led us to restrict the set of genes for each of the two studies. A more efficient implementation or alternative approaches such as FlashAttention (Dao et al., 2022) can lead to better ability to utilize all genes profiled.

REFERENCES

- Amr Ahmed and Eric P. Xing. Recovering time-varying networks of dependencies in social and biological studies. *Proceedings of the National Academy of Sciences*, 106(29):11878–11883, July 2009.
- Christof Angermueller, Tanel Pärnamaa, Leopold Parts, and Oliver Stegle. Deep learning for computational biology. *Mol. Syst. Biol.*, 12(7):878, July 2016.
- Pau Badia-I-Mompel, Lorna Wessels, Sophia Müller-Dott, Rémi Trimbour, Ricardo O Ramirez Flores, Ricard Argelaguet, and Julio Saez-Rodriguez. Gene regulatory network inference in the era of single-cell multi-omics. *Nat. Rev. Genet.*, 24(11):739–754, November 2023.
- Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv [cs.CL]*, September 2014.
- Ziv Bar-Joseph, Georg K. Gerber, Tong Ihn Lee, Nicola J. Rinaldi, Jane Y. Yoo, François Robert, D. Benjamin Gordon, Ernest Fraenkel, Tommi S. Jaakkola, Richard A. Young, and David K. Gifford. Computational discovery of gene modules and regulatory networks. *Nature Biotechnology*, 21(11):1337–1342, November 2003.
- Ziv Bar-Joseph, Anthony Gitter, and Itamar Simon. Studying and modelling dynamic biological processes using time-series gene expression data. *Nat. Rev. Genet.*, 13(8):552–564, July 2012.
- Y Benjamini and Y Hochberg. Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the royal statistical society series b-methodological*, 57(1): 289–300, 1995.
- Alexandre Blais and Brian David Dynlacht. Constructing transcriptional regulatory networks. *Genes & Development*, 19(13):1499–1511, July 2005.
- Cătălina Cangea, Petar Veličković, Nikola Jovanović, Thomas Kipf, and Pietro Liò. Towards sparse hierarchical graph classifiers. *arXiv [stat.ML]*, November 2018.
- Thalia E Chan, Michael P H Stumpf, and Ann C Babtie. Gene regulatory network inference from single-cell data using multivariate information measures. *Cell Syst.*, 5(3):251–267.e3, September 2017.
- Deborah Chasman and Sushmita Roy. Inference of cell type specific regulatory networks on mammalian lineages. *Curr. Opin. Syst. Biol.*, 2:130–139, April 2017.
- Travers Ching, Daniel S Himmelstein, Brett K Beaulieu-Jones, Alexandr A Kalinin, Brian T Do, Gregory P Way, Enrico Ferrero, Paul-Michael Agapow, Michael Zietz, Michael M Hoffman, Wei Xie, Gail L Rosen, Benjamin J Lengerich, Johnny Israeli, Jack Lanchantin, Stephen Woloszynek, Anne E Carpenter, Avanti Shrikumar, Jinbo Xu, Evan M Cofer, Christopher A Lavender, Srinivas C Turaga, Amr M Alexandari, Zhiyong Lu, David J Harris, Dave DeCaprio, Yanjun Qi, Anshul Kundaje, Yifan Peng, Laura K Wiley, Marwin H S Segler, Simina M Boca, S Joshua Swamidass, Austin Huang, Anthony Gitter, and Casey S Greene. Opportunities and obstacles for deep learning in biology and medicine. J. R. Soc. Interface, 15(141), April 2018.
- Tri Dao, Daniel Y Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. *arXiv* [cs.LG], May 2022.
- Jun Ding, Nadav Sharon, and Ziv Bar-Joseph. Temporal modelling using single-cell transcriptomics. *Nature Reviews Genetics*, 23(6):355–368, June 2022.
- Frank Dondelinger, Sophie Lèbre, and Dirk Husmeier. Non-homogeneous dynamic Bayesian networks with Bayesian regularization for inferring gene regulatory networks with gradually timevarying structure. *Machine Learning*, 90(2):191–230, February 2013.
- Susan Elmore. Apoptosis: a review of programmed cell death. *Toxicol. Pathol.*, 35(4):495–516, June 2007.

- Zhuoqing Fang, Xinyuan Liu, and Gary Peltz. GSEApy: a comprehensive package for performing gene set enrichment analysis in python. *Bioinformatics*, 39(1):btac757, January 2023.
- Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. *arXiv [cs.LG]*, pp. 1126–1135, March 2017.
- R A Fisher. On the interpretation of χ^2 from contingency tables, and the calculation of P. J. R. Stat. Soc., 85(1):87, January 1922.
- A P Gasch, P T Spellman, C M Kao, O Carmel-Harel, M B Eisen, G Storz, D Botstein, and P O Brown. Genomic expression programs in the response of yeast cells to environmental changes. *Mol. Biol. Cell*, 11(12):4241–4257, December 2000.
- Daniel A. Gilchrist, David C. Fargo, and Karen Adelman. Using ChIP-chip and ChIP-seq to study the regulation of gene expression: Genome-wide localization studies reveal widespread regulation of transcription elongation. *Methods*, 48(4):398–408, August 2009.
- Dhouha Grissa, Alexander Junge, Tudor I Oprea, and Lars Juhl Jensen. Diseases 2.0: a weekly updated database of disease-gene associations from text mining and data integration. *Database* (*Oxford*), 2022:baac019, March 2022.
- Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. *arXiv* [cs.LG], October 2021.
- David Hallac, Youngsuk Park, Stephen Boyd, and Jure Leskovec. Network inference via the timevarying graphical lasso. *KDD*, 2017:205–213, August 2017.
- Heonjong Han, Jae-Won Cho, Sangyoung Lee, Ayoung Yun, Hyojin Kim, Dasom Bae, Sunmo Yang, Chan Yeong Kim, Muyoung Lee, Eunbeen Kim, Sungho Lee, Byunghee Kang, Dabin Jeong, Yaeji Kim, Hyeon-Nae Jeon, Haein Jung, Sunhwee Nam, Michael Chung, Jong-Hoon Kim, and Insuk Lee. TRRUST v2: an expanded reference database of human and mouse transcriptional regulatory interactions. *Nucleic Acids Res.*, 46(D1):D380–D386, January 2018.
- Sandra L Harris and Arnold J Levine. The p53 pathway: positive and negative feedback loops. *Oncogene*, 24(17):2899–2908, April 2005.
- Matthew S Hayden and Sankar Ghosh. NF-kb in immunobiology. *Cell Res.*, 21(2):223–244, February 2011.
- Kerry L Hilligan, Sivaranjani Namasivayam, Chad S Clancy, Paul J Baker, Samuel I Old, Victoria Peluf, Eduardo P Amaral, Sandra D Oland, Danielle O'Mard, Julie Laux, Melanie Cohen, Nicole L Garza, Bernard A P Lafont, Reed F Johnson, Carl G Feng, Dragana Jankovic, Olivier Lamiable, Katrin D Mayer-Barber, and Alan Sher. Bacterial-induced or passively administered interferon gamma conditions the lung for early control of SARS-CoV-2. *Nat. Commun.*, 14(1): 8229, December 2023.
- Vân Anh Huynh-Thu, Alexandre Irrthum, Louis Wehenkel, and Pierre Geurts. Inferring regulatory networks from expression data using tree-based methods. *PLoS One*, 5(9):e12776, September 2010.
- Aashi Jindal, Prashant Gupta, Jayadeva, and Debarka Sengupta. Discovery of rare cells from voluminous single cell expression data. *Nat. Commun.*, 9(1):4719, November 2018.
- Kenji Kamimoto, Blerta Stringa, Christy M Hoffmann, Kunal Jindal, Lilianna Solnica-Krezel, and Samantha A Morris. Dissecting cell identity via network inference and in silico gene perturbation. *Nature*, 614(7949):742–751, February 2023.
- Guy Karlebach and Ron Shamir. Modelling and analysis of gene regulatory networks. *Nat. Rev. Mol. Cell Biol.*, 9(10):770–780, October 2008.
- Man-Sun Kim, Jeong-Rae Kim, Dongsan Kim, Arthur D. Lander, and Kwang-Hyun Cho. Spatiotemporal network motif reveals the biological traits of developmental gene regulatory networks in Drosophila melanogaster. *BMC Systems Biology*, 6(1):31, May 2012.

- Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv* [cs.LG], December 2014.
- Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3744–3753. PMLR, 2019.
- Tong Ihn Lee, Nicola J. Rinaldi, François Robert, Duncan T. Odom, Ziv Bar-Joseph, Georg K. Gerber, Nancy M. Hannett, Christopher T. Harbison, Craig M. Thompson, Itamar Simon, Julia Zeitlinger, Ezra G. Jennings, Heather L. Murray, D. Benjamin Gordon, Bing Ren, John J. Wyrick, Jean-Bosco Tagne, Thomas L. Volkert, Ernest Fraenkel, David K. Gifford, and Richard A. Young. Transcriptional Regulatory Networks in Saccharomyces cerevisiae. *Science*, 298(5594):799–804, October 2002.
- Arthur Liberzon, Chet Birger, Helga Thorvaldsdóttir, Mahmoud Ghandi, Jill P Mesirov, and Pablo Tamayo. The molecular signatures database (MSigDB) hallmark gene set collection. *Cell Syst.*, 1(6):417–425, December 2015.
- Zhi-Ping Liu, Canglin Wu, Hongyu Miao, and Hulin Wu. RegNetwork: an integrated database of transcriptional and post-transcriptional regulatory networks in human and mouse. *Database (Oxford)*, 2015:bav095, September 2015.
- Nicholas M Luscombe, M Madan Babu, Haiyuan Yu, Michael Snyder, Sarah A Teichmann, and Mark Gerstein. Genomic analysis of regulatory network dynamics reveals large topological changes. *Nature*, 431(7006):308–312, September 2004.
- Hirotaka Matsumoto, Hisanori Kiryu, Chikara Furusawa, Minoru S H Ko, Shigeru B H Ko, Norio Gouda, Tetsutaro Hayashi, and Itoshi Nikaido. SCODE: an efficient regulatory network inference algorithm from single-cell RNA-seq during differentiation. *Bioinformatics*, 33(15):2314–2321, August 2017a.
- Hirotaka Matsumoto, Hisanori Kiryu, Chikara Furusawa, Minoru S H Ko, Shigeru B H Ko, Norio Gouda, Tetsutaro Hayashi, and Itoshi Nikaido. SCODE: An efficient regulatory network inference algorithm from single-cell RNA-Seq during differentiation. *Bioinformatics*, 33(15):2314–2321, August 2017b.
- Thomas Moerman, Sara Aibar Santos, Carmen Bravo González-Blas, Jaak Simm, Yves Moreau, Jan Aerts, and Stein Aerts. GRNBoost2 and arboreto: efficient and scalable inference of gene regulatory networks. *Bioinformatics*, 35(12):2159–2161, June 2019.
- Hung Nguyen, Duc Tran, Bang Tran, Bahadir Pehlivan, and Tin Nguyen. A comprehensive survey of regulatory network inference methods using single cell RNA sequencing data. *Briefings in Bioinformatics*, 22(3):bbaa190, May 2021.
- Aldo Pareja, Giacomo Domeniconi, Jie Chen, Tengfei Ma, Toyotaro Suzumura, Hiroki Kanezashi, Tim Kaler, Tao Schardl, and Charles Leiserson. EvolveGCN: Evolving graph convolutional networks for dynamic graphs. *Proc. Conf. AAAI Artif. Intell.*, 34(04):5363–5370, April 2020.
- Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. *arXiv [cs.LG]*, November 2012.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Köpf, Edward Yang, Zach DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An imperative style, high-performance deep learning library. arXiv [cs.LG], December 2019.
- Sune Pletscher-Frankild, Albert Pallejà, Kalliopi Tsafou, Janos X Binder, and Lars Juhl Jensen. DISEASES: text mining and data integration of disease-gene associations. *Methods*, 74:83–89, March 2015.

- Aditya Pratapa, Amogh P Jalihal, Jeffrey N Law, Aditya Bharadwaj, and T M Murali. Benchmarking algorithms for gene regulatory network inference from single-cell transcriptomic data. *Nat. Methods*, 17(2):147–154, February 2020.
- Aviv Regev, Sarah A Teichmann, Eric S Lander, Ido Amit, Christophe Benoist, Ewan Birney, Bernd Bodenmiller, Peter Campbell, Piero Carninci, Menna Clatworthy, Hans Clevers, Bart Deplancke, Ian Dunham, James Eberwine, Roland Eils, Wolfgang Enard, Andrew Farmer, Lars Fugger, Berthold Göttgens, Nir Hacohen, Muzlifah Haniffa, Martin Hemberg, Seung Kim, Paul Klenerman, Arnold Kriegstein, Ed Lein, Sten Linnarsson, Emma Lundberg, Joakim Lundeberg, Partha Majumder, John C Marioni, Miriam Merad, Musa Mhlanga, Martijn Nawijn, Mihai Netea, Garry Nolan, Dana Pe'er, Anthony Phillipakis, Chris P Ponting, Stephen Quake, Wolf Reik, Orit Rozenblatt-Rosen, Joshua Sanes, Rahul Satija, Ton N Schumacher, Alex Shalek, Ehud Shapiro, Padmanee Sharma, Jay W Shin, Oliver Stegle, Michael Stratton, Michael J T Stubbington, Fabian J Theis, Matthias Uhlen, Alexander van Oudenaarden, Allon Wagner, Fiona Watt, Jonathan Weissman, Barbara Wold, Ramnik Xavier, Nir Yosef, and Human Cell Atlas Meeting Participants. The human cell atlas. *Elife*, 6, December 2017.
- Dominik Saul, Robyn Laura Kosinsky, Elizabeth J Atkinson, Madison L Doolittle, Xu Zhang, Nathan K LeBrasseur, Robert J Pignolo, Paul D Robbins, Laura J Niedernhofer, Yuji Ikeno, Diana Jurk, João F Passos, Latonya J Hickson, Ailing Xue, David G Monroe, Tamara Tchkonia, James L Kirkland, Joshua N Farr, and Sundeep Khosla. A new gene set identifies senescent cells and predicts senescence-associated pathways across tissues. *Nat. Commun.*, 13(1):4827, August 2022.
- Marcel H. Schulz, William E. Devanny, Anthony Gitter, Shan Zhong, Jason Ernst, and Ziv Bar-Joseph. DREM 2.0: Improved reconstruction of dynamic regulatory networks from time-series expression data. *BMC Systems Biology*, 6(1):104, August 2012.
- Lucas Seninge, Ioannis Anastopoulos, Hongxu Ding, and Joshua Stuart. VEGA is an interpretable generative model for inferring biological network activity in single-cell transcriptomics. *Nat. Commun.*, 12(1):5684, September 2021.
- SenNet Consortium. NIH SenNet consortium to map senescent cells throughout the human lifespan to understand physiological health. *Nat Aging*, 2(12):1090–1100, December 2022.
- Harsh Shrivastava, Xiuwei Zhang, Le Song, and Srinivas Aluru. GRNUlar: A deep learning framework for recovering single-cell gene regulatory networks. *J. Comput. Biol.*, 29(1):27–44, January 2022.
- Hantao Shu, Jingtian Zhou, Qiuyu Lian, Han Li, Dan Zhao, Jianyang Zeng, and Jianzhu Ma. Modeling gene regulatory networks using neural network architectures. *Nat. Comput. Sci.*, 1(7):491–501, July 2021.
- Lisa Sikkema, Ciro Ramírez-Suástegui, Daniel C Strobl, Tessa E Gillett, Luke Zappia, Elo Madissoon, Nikolay S Markov, Laure-Emmanuelle Zaragosi, Yuge Ji, Meshal Ansari, Marie-Jeanne Arguel, Leonie Apperloo, Martin Banchero, Christophe Bécavin, Marijn Berg, Evgeny Chichelnitskiy, Mei-I Chung, Antoine Collin, Aurore C A Gay, Janine Gote-Schniering, Baharak Hooshiar Kashani, Kemal Inecik, Manu Jain, Theodore S Kapellos, Tessa M Kole, Sylvie Leroy, Christoph H Mayr, Amanda J Oliver, Michael von Papen, Lance Peter, Chase J Taylor, Thomas Walzthoeni, Chuan Xu, Linh T Bui, Carlo De Donno, Leander Dony, Alen Faiz, Minzhe Guo, Austin J Gutierrez, Lukas Heumos, Ni Huang, Ignacio L Ibarra, Nathan D Jackson, Preetish Kadur Lakshminarasimha Murthy, Mohammad Lotfollahi, Tracy Tabib, Carlos Talavera-López, Kyle J Travaglini, Anna Wilbrey-Clark, Kaylee B Worlock, Masahiro Yoshida, Lung Biological Network Consortium, Maarten van den Berge, Yohan Bossé, Tushar J Desai, Oliver Eickelberg, Naftali Kaminski, Mark A Krasnow, Robert Lafyatis, Marko Z Nikolic, Joseph E Powell, Jayaraj Rajagopal, Mauricio Rojas, Orit Rozenblatt-Rosen, Max A Seibold, Dean Sheppard, Douglas P Shepherd, Don D Sin, Wim Timens, Alexander M Tsankov, Jeffrey Whitsett, Yan Xu, Nicholas E Banovich, Pascal Barbry, Thu Elizabeth Duong, Christine S Falk, Kerstin B Meyer, Jonathan A Kropski, Dana Pe'er, Herbert B Schiller, Purushothama Rao Tata, Joachim L Schultze, Sara A Teichmann, Alexander V Misharin, Martijn C Nawijn, Malte D Luecken, and Fabian J Theis. An integrated cell atlas of the lung in health and disease. Nat. Med., 29(6):1563–1577, June 2023.

- Edwin K Silverman, Harald H H W Schmidt, Eleni Anastasiadou, Lucia Altucci, Marco Angelini, Lina Badimon, Jean-Luc Balligand, Giuditta Benincasa, Giovambattista Capasso, Federica Conte, Antonella Di Costanzo, Lorenzo Farina, Giulia Fiscon, Laurent Gatto, Michele Gentili, Joseph Loscalzo, Cinzia Marchese, Claudio Napoli, Paola Paci, Manuela Petti, John Quackenbush, Paolo Tieri, Davide Viggiano, Gemma Vilahur, Kimberly Glass, and Jan Baumbach. Molecular networks in network medicine: Development and applications. *Wiley Interdiscip. Rev. Syst. Biol. Med.*, 12(6):e1489, November 2020.
- Le Song, Mladen Kolar, and Eric Xing. Time-Varying Dynamic Bayesian Networks. In Advances in Neural Information Processing Systems, volume 22. Curran Associates, Inc., 2009.
- Maximilian Strunz, Lukas M Simon, Meshal Ansari, Jaymin J Kathiriya, Ilias Angelidis, Christoph H Mayr, George Tsidiridis, Marius Lange, Laura F Mattner, Min Yee, Paulina Ogar, Arunima Sengupta, Igor Kukhtevich, Robert Schneider, Zhongming Zhao, Carola Voss, Tobias Stoeger, Jens H L Neumann, Anne Hilgendorff, Jürgen Behr, Michael O'Reilly, Mareike Lehmann, Gerald Burgstaller, Melanie Königshoff, Harold A Chapman, Fabian J Theis, and Herbert B Schiller. Alveolar regeneration through a Krt8+ transitional stem cell state that persists in human lung fibrosis. *Nat. Commun.*, 11(1):3559, July 2020.
- Aravind Subramanian, Pablo Tamayo, Vamsi K Mootha, Sayan Mukherjee, Benjamin L Ebert, Michael A Gillette, Amanda Paulovich, Scott L Pomeroy, Todd R Golub, Eric S Lander, and Jill P Mesirov. Gene set enrichment analysis: a knowledge-based approach for interpreting genomewide expression profiles. *Proc. Natl. Acad. Sci. U. S. A.*, 102(43):15545–15550, October 2005.
- Vidyani Suryadevara, Adam D Hudgins, Adarsh Rajesh, Alberto Pappalardo, Alla Karpova, Amit K Dey, Ann Hertzel, Anthony Agudelo, Azucena Rocha, Bikem Soygur, Birgit Schilling, Chase M Carver, Cristina Aguayo-Mazzucato, Darren J Baker, David A Bernlohr, Diana Jurk, Dilyana B Mangarova, Ellen M Quardokus, Elizabeth Ann L Enninga, Elizabeth L Schmidt, Feng Chen, Francesca E Duncan, Francesco Cambuli, Gagandeep Kaur, George A Kuchel, Gung Lee, Heike E Daldrup-Link, Helene Martini, Hemali Phatnani, Iman M Al-Naggar, Irfan Rahman, Jia Nie, João F Passos, Jonathan C Silverstein, Judith Campisi, Julia Wang, Kanako Iwasaki, Karina Barbosa, Kay Metis, Kerem Nernekli, Laura J Niedernhofer, Li Ding, Lichao Wang, Lisa C Adams, Liu Ruiyang, Madison L Doolittle, Marcos G Teneche, Marissa J Schafer, Ming Xu, Mohammadjavad Hajipour, Mozhgan Boroumand, Nathan Basisty, Nicholas Sloan, Nikolai Slavov, Olena Kuksenko, Paul Robson, Paul T Gomez, Periklis Vasilikos, Peter D Adams, Priscila Carapeto, Ouan Zhu, Ramalakshmi Ramasamy, Rolando Perez-Lorenzo, Rong Fan, Runze Dong, Ruth R Montgomery, Sadiya Shaikh, Sanja Vickovic, Shanshan Yin, Shoukai Kang, Sonja Suvakov, Sundeep Khosla, Vesna D Garovic, Vilas Menon, Yanxin Xu, Yizhe Song, Yousin Suh, Zhixun Dou, and Nicola Neretti. SenNet recommendations for detecting senescent cells in different tissues. Nat. Rev. Mol. Cell Biol., pp. 1-23, June 2024.
- Siyi Tang, Jared A Dunnmon, Liangqiong Qu, Khaled K Saab, Tina Baykaner, Christopher Lee-Messer, and Daniel L Rubin. Modeling multivariate biosignals with graph neural networks and structured state space models. *arXiv* [cs.LG], November 2022.
- Jan M van Deursen. The role of senescent cells in ageing. Nature, 509(7501):439-446, May 2014.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. Advances in Neural Information Processing Systems, 30, 2017.
- Huihui Wang, Yongqing Wu, Ruiling Fang, Jian Sa, Zhi Li, Hongyan Cao, and Yuehua Cui. Time-Varying Gene Network Analysis of Human Prefrontal Cortex Development. *Frontiers in Genetics*, 11, 2020.
- Jiacheng Wang, Yaojia Chen, and Quan Zou. Inferring gene regulatory network from single-cell transcriptomes with graph autoencoder model. *PLoS Genet.*, 19(9):e1010942, September 2023a.
- Lingfei Wang, Nikolaos Trasanidis, Ting Wu, Guanlan Dong, Michael Hu, Daniel E Bauer, and Luca Pinello. Dictys: dynamic gene regulatory network dissects developmental continuum with single-cell multiomics. *Nat. Methods*, 20(9):1368–1378, September 2023b.

- Yong Wang, Trupti Joshi, Xiang-Sun Zhang, Dong Xu, and Luonan Chen. Inferring gene regulatory networks from multiple microarray datasets. *Bioinformatics*, 22(19):2413–2420, October 2006.
- Zhong Wang, Mark Gerstein, and Michael Snyder. RNA-Seq: A revolutionary tool for transcriptomics. *Nature Reviews Genetics*, 10(1):57–63, January 2009.
- Aaron Wise and Ziv Bar-Joseph. cDREM: inferring dynamic combinatorial gene regulation. J. Comput. Biol., 22(4):324–333, April 2015.
- Min Yan, Jing Hu, Huating Yuan, Liwen Xu, Gaoming Liao, Zedong Jiang, Jiali Zhu, Bo Pang, Yanyan Ping, Yunpeng Zhang, Yun Xiao, and Xia Li. Dynamic regulatory networks of T cell trajectory dissect transcriptional control of T cell state transition. *Molecular Therapy Nucleic Acids*, 26:1115–1129, December 2021.
- Nir Yosef, Alex K. Shalek, Jellert T. Gaublomme, Hulin Jin, Youjin Lee, Amit Awasthi, Chuan Wu, Katarzyna Karwacz, Sheng Xiao, Marsela Jorgolli, David Gennert, Rahul Satija, Arvind Shakya, Diana Y. Lu, John J. Trombetta, Meenu R. Pillai, Peter J. Ratcliffe, Mathew L. Coleman, Mark Bix, Dean Tantin, Hongkun Park, Vijay K. Kuchroo, and Aviv Regev. Dynamic regulatory network controlling TH17 cell differentiation. *Nature*, 496(7446):461–468, April 2013.
- Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. *Advances in Neural Information Processing Systems*, 30, 2017.
- Bingjie Zhang, Rabi Upadhyay, Yuhan Hao, Marie I Samanovic, Ramin S Herati, John D Blair, Jordan Axelrad, Mark J Mulligan, Dan R Littman, and Rahul Satija. Multimodal single-cell datasets characterize antigen-specific CD8+ T cells across SARS-CoV-2 vaccination and infection. *Nat. Immunol.*, 24(10):1725–1734, October 2023.
- Qi Zhang, Jianlong Chang, Gaofeng Meng, Shiming Xiang, and Chunhong Pan. Spatio-temporal graph structure learning for traffic forecasting. *Proc. Conf. AAAI Artif. Intell.*, 34(01):1177–1185, April 2020.
- Shijia Zhu and Yadong Wang. Hidden Markov induced Dynamic Bayesian Network for recovering time evolving gene regulatory networks. *Scientific Reports*, 5(1):17841, December 2015.
- Yanqiao Zhu, Weizhi Xu, Jinghao Zhang, Yuanqi Du, Jieyu Zhang, Qiang Liu, Carl Yang, and Shu Wu. A survey on graph structure learning: Progress and opportunities. *arXiv* [cs.LG], March 2021.

A APPENDIX

A.1 SET TRANSFORMER OPERATIONS

We redefine the Multihead and rFF operations from Set Transformers (Lee et al., 2019) to the ones used for Marlene here.

First, we define the **Attention** operation. Let $Q \in \mathbb{R}^{k \times g}$ be the query matrix of k elements and g dimensions. The Attention operation used for MAB is

Attention
$$(Q, K, V) = \operatorname{softmax}\left(\frac{QK^{\top}}{\sqrt{g}}\right)V$$
 (8)

where the key and value matrices are $K, V \in \mathbb{R}^{c \times g}$. Next, the Multihead attention operation with h heads (Vaswani et al., 2017) is given by

$$Multihead(Q, K, V) = concat(O_1, \dots, O_h)W^O$$
(9)

where $O_j = \text{Attention}(QW_j^Q, KW_j^K, VW_j^V)$ for weight matrices $W_j^Q, W_j^K, W_j^V \in \mathbb{R}^{g \times g/h}$ and $W^O \in \mathbb{R}^{g \times g}$ (these matrices are not to be confused with self-attention weights used consequently for Marlene). In our implementation, k is the number of seeds or output vectors used for the PMA layer. This is a hyperparameter that corresponds to the number of "statistic" vectors we expect to learn from data. Finally, rFF is a feedfoward layer such as a linear layer.

A.2 EVOLVEGCN OPERATIONS

Here, we introduce the GRU and topK pooling operations used in the second step of Marlene.

The topK pooling operation is needed to summarize nodes into k representative ones (Cangea et al., 2018; Pareja et al., 2020). Here k is the same as the number of seeds used for PMA. Given an input $\mathbf{G} \in \mathbb{R}^{g \times k}$ and a learnable vector q, the TopK operation performs the following steps:

$$\begin{split} \rho &= \frac{\mathbf{G}q}{\|q\|} \\ i &= \mathrm{Top-k-indices}(\rho) \\ \mathbf{Z} &= [\mathbf{G} \odot \tanh{(\rho)}]_i. \end{split}$$

At time step t, given a pooled matrix \mathbf{Z}_t and hidden state \mathbf{W}_{t-1} (i.e., self-attention weights \mathbf{W}_{t-1}^Q or \mathbf{W}_{t-1}^K), the standard GRU operation is:

$$r_t = \sigma(M_{ir}\mathbf{Z}_t + b_{ir} + M_{hr}\mathbf{W}_{t-1} + b_{hr})$$

$$z_t = \sigma(M_{iz}\mathbf{Z}_t + b_{iz} + M_{hz}\mathbf{W}_{t-1} + b_{hz})$$

$$n_t = \tanh(M_{in}\mathbf{Z}_t + b_{in} + r_t \odot (M_{hn}\mathbf{W}_{t-1} + b_{hn}))$$

$$\mathbf{W}_t = (1 - z_t) \odot n_t + z_t \odot \mathbf{W}_{t-1}$$

where σ is the sigmoid function and \odot is the Hadamard product. See also Paszke et al. (2019).

A.3 SUPPLEMENTARY FIGURE FOR THE HLCA DATASET



Figure 6: (a) FDR corrected *p*-values of Fisher exact tests reflecting the number of links that overlap with the two TF-gene databases. (b) IoU scores across time reflecting the overlap between consecutive graphs.



A.4 ANALYSIS OF THE FIBROSIS DATASET

Figure 7: (a) FDR corrected *p*-values of Fisher exact tests reflecting the number of links that overlap with the two mouse databases. (b) IoU scores across time reflecting the overlap between consecutive graphs.